PA series



PA-1500

DESCRIPTION

The PA series amplifiers are designed and built to provide an affordable, quality powering solution. The wide range of models makes the series ideal for both installed or mobile sound reinforcement applications.

The amplifiers incorporate a rugged 2 unit all-steel chassis ensuring structural rigidity. The low-noise fans offer both quiet and cool operation. The amplifier incorporates rear located switches which permit, operational mode selection (bridge, stereo or parallel) and input sensitivity selection.

KEY FEATURES

- \cdot Input Sensitivity Selector
- $\cdot\,750$ W x 750 W at 4 Ω
- \cdot SpeakON output connectors
- \cdot Clip, protection and signal present LED indicators

APPLICATIONS

- · Live sound reinforcement
- $\boldsymbol{\cdot}$ Bands, DJ's and performers
- Speech and vocals
- \cdot Music playback in entertainment
- \cdot A/V, conferences and presentations

SPECIFICATIONS

Output Power Ratings

Power 8 Ohms, Both Channels Driven	2 x 500 W
Power 8 Ohms Bridged	1500 W
Power 4 Ohms, Both Channels Driven	2 x 750 W

Electronics and Connectors

2	
20 Hz - 20 kHz, +0 - 1 dB	
<0.5% , 20 Hz - 20 kHz	
>100 dB @ 20 Hz - 20 kZ	
33 dB	
> 200 @ 10 Hz - 400 Hz	
Power On/Off, Gain Pots	
Internal heat sinks with forced air: Fan cooled	
Protection against short circuits, no-load, on/off muting, RF interference.	
Power, Protection, Signal, Clip	
2 x Female XLR	
2 x Male XLR	
2 x speakON	
IEC	
180-250 VAC	
7.5 A	



PA-1500

Dimensions-Weight

Dimensions (H x W x D)	88 x 482 x 227 mm 3,5 x 19,0 x 8,9 in
Net Weight	13,5 kg (29,8 lb)
Shipping Carton Dimensions (H x W x D)	160 x 580 x 540 mm 6,3 x 22,8 x 21,3 in
Shipping Weight	14,0 kg (30,8 lb)

ORDERING INFORMATION

Performance				
Model	Description	P/N		
System				
PA-1500		10717120		

DIMENSIONS



