

BTM-S06R & BTM-S05T

Bluetooth Microphone Voice Enhancement System



FEATURES

BTM-S05T Transmitter (3.5mm mono Female connector)
BTM-S06R Receiver (6.3mm mono Male plug)

- Plug-N-Play
- High quality transmission
- No movement restriction
- Convenient and portable
- User friendly

TECHNICAL SPECIFICATION

Bluetooth standard: Bluetooth specification V2.0
Output power: Class 1
Transmission distance: 35meters (Unobstructed line of sight)
Battery: AAA size 4pcs (TX 2pcs, RX 2pcs)
Battery life: Approximately 8 hours
Carrier band frequency: ISM band 2,400~2,483.5 MHz
Transmit power: +5dBm
Receiver sensitivity: -85dBm
Maximum output voltage: 110mV (RMS)
Maximum current consumption: 70mA
Frequency response: 25~19KHz (BTM-S05T)
32~19KHz (BTM-S06R)
Latency: ~4 ms (Millisecond)

BTM-S06R & BTM-S06T

Bluetooth Microphone Voice Enhancement System



FEATURES

BTM-S06T Transmitter (XLR Female connector)
BTM-S06R Receiver (6.3mm mono Male plug)

- Plug-N-Play
- High quality transmission
- No movement restriction
- Convenient and portable
- User friendly

TECHNICAL SPECIFICATION

Bluetooth standard: Bluetooth specification V2.0
Output power: Class 1
Transmission distance: 35meters (Unobstructed line of sight)
Battery: AAA size 4pcs (TX 2pcs, RX 2pcs)
Battery life: Approximately 8 hours
Carrier band frequency: ISM band 2,400~2,483.5 MHz
Transmit power: +5dBm
Receiver sensitivity: -85dBm
Maximum output voltage: 110mV (RMS)
Maximum current consumption: 70mA
Frequency response: 25~19KHz (BTM-S06T)
32~19KHz (BTM-S06R)
Latency: ~4 ms (Millisecond)

* Specifications are subject to changes without notice.